

# Hosted-iFrame Mode - Table of request attributes

## Table of request-attributes

These attributes and values are allowed in object "request":

attribute	value
request	fixed value: 'creditcardcheck'
responsetype	fixed value: 'JSON'
storecarddata	fixed value: 'yes'
mode	mode for transactions, either 'live' or 'test'
encoding	your encoding, either 'ISO-8859-1' or 'UTF-8'
mid	your Merchant ID
aid	your Account ID
portalid	your Portal ID
checktype	optional configuration - valid for Deutsche Bahn only Fixed value "TC" -> starting "creditcardcheck with travel cards"
hash	MD5 or sha2_384 hash over request values (alphabetical order) plus portal key in your PMI portal configuration. e.g.: <ul style="list-style-type: none"><li>• aid: '10002', // your AID</li><li>• encoding: 'UTF-8', // desired encoding</li><li>• mid: '10001', // your MID</li><li>• mode: 'live', // desired mode</li><li>• portalid: '2000002', // your PortalId</li><li>• request: 'creditcardcheck', // fixed value</li><li>• responsetype: 'JSON', // fixed value</li><li>• storecarddata: 'yes', // fixed value</li><li>• PMI Portal key: '123456'</li></ul> MD5("10002UTF-810001live2000002creditcardcheckJSONyes123456") =5c4014cebeb361d9e186fd42c810b9b1 or hash_hmac("sha384", "10002UTF-810001live2000002creditcardcheckJSONyes", "123456") =1cf456bf692453613ebb992a3fb859cc347ddc7e94e2ca764efbe8b0089de6964ab1266df0831e59de89dc5291070fe7